

Implementing Neural Networks on Memory-based Reconfigurable Logic Device (MRLD)

Xihong ZHOU, Senling WANG, Yoshinobu HIGAMI, Hiroshi TAKAHASHI

Department of Computer Science, Ehime University

Masayuki SATO, Mitsunori KATSU

TRL Co., Ltd.

Shoichi SEKIGUCHI

TAIYO YUDEN CO., LTD.

September 18, 2020

Outline

- Introduction
- What is MRLD
- The basic operation of Neuron in MRLD
- MRLD-based Neural Network: MNN
- Experimental results
- Conclusions


Background

- Neural networks (NNs) algorithm has achieved significant contributions.
 - Computer vision, speech recognition, robotics.



Background

- NNs usually with **Millions of parameters** → requires **high-performance** computing device.
- **Hardware design** for NNs is gaining great attentions.
- GPUs: high speed, high power, ASIC: low power, high development cost .
- **Reconfigurable devices**: flexible and scalable (such as FPGA) .



Neural Network Accelerator Comparison

<http://nicsefc.ee.tsinghua.edu.cn/projects/neural-network-accelerator/>


Background

- For edge devices
(e.g.: battery-powered mobile devices, robots, etc.) → high-performance, low power is required.



Background

- MRLD is a new type of **reconfigurable device**.
- Compared with existing technology FPGA, **high speed, low power**, and **low cost**.



5 times faster than FPGA and 1/10 the power consumption

<https://xtech.nikkei.com/dm/atcl/event/15/091100139/100200019/>


	GPGUs	ASICs	FPGAs	MRLDs
high speed	○	△	△	○
low power	✗	◇	△	○
Flexible and scalable	△	✗	○	○

Expression degree: ○ > ◇ > △ > ✗

https://www.yuden.co.jp/resource/data/ProductMovie/jp/MRLD_PV_Yuden_J_S_1807.mp4

Motivation & Purpose & Objective

- MRLD is a promising alternative Edge AI device for NNs application.



- Purpose



Develop the approaches for implementing the neural network into the MRLD

- Objective

1. **Analyzing the basic operation of NN neurons in MRLD**
2. **Propose a novel network structure to adapt the special structure of MRLD**


What is MRLD

- An MRLD (Memory-based Reconfigurable Logic Device) is composed of multiple general-purpose memory cells (MLUTs: Multiple Look Up Tables) arranged in an array.



How an MRLD works




- Configure the logic circuit by writing the **truth table** of the logic circuit (including wiring logic) to the SRAM of MLUT



The traditional hardware design for NNs

- The multiply-accumulate operation circuit , memory are necessary for NNs hardware design in traditional design method.


$$u = \sum_0^N w_i * x_i + b$$
$$y = f(u)$$



Traditional hardware design: Multiply-add and memory for neuron


The basic operation of Neuron in MRLD

- The weights can be extracted and form a mapping for x and output y .





The basic operation of Neuron in MRLD

- In MRLD, the NN neurons can be calculated in truth table form by binarizing inputs and outputs of NN which does not require constructing any logic circuits.




For the MRLD structure: Traditional NN is not suitable

- It's difficult to construct the traditional NN into the MRLD with the fully connection way




MLUT connection structure in MRLD



To adapt the MRLD structure: MNN (MRLD-based Neural Network)





MRLD-based Neural Network: MNN



Experimental results (using MNIST)--The MNN and FNN training result in 100 epochs



Experimental results (using MNIST)-- The MNN training result in 700 epochs



Conclusions

- Introduced the MRLD device which is applied the next-generation Edge AI devices.
- Analyzed the NN neuron's operation principle in MRLD
- Proposed a novel network structure MNN (MRLD-based Neural Network) to adapt the MRLD structure
- Performed a recognition training experiment using the MNIST dataset to confirm the effectiveness of the MNN.
- In our future work, we will analyze and design the method for image and data of any size that can be recognized in MNN in MRLD

Thank you for your listening